Single and Combined Fiber Doors





Exterior fiber doors collection is distinct by his authentic wood appearance that gives prestigious looking. Made of high definition fiberglass, his finish can be combined with a wide array of decorative glazing. Also, adding a lateral panel to Single door will offer a better luminosity and will give character to your project.

Single and Combined fiber doors use only the very finest materials to offer maximum security, efficient insulation, and impeccable ease of use.

OPTIONS

Frames

- Thickness choice*
- Depth choice*
- 118 mm to 235 mm (4 ⁵/₈" to 9 ¹/₄")

Glazing

- Double glazing
- Triple-sealed glazing
- Decorative glazing
- Energy efficient glass

Brickmoulds

- Pine
- PVC
- Aluminum (color selection)

Exterior Cladding

- PVC
- Aluminum (color selection)

Interior Cladding

■ PVC

Sills

- Depth choice*
- = 50 mm (2") sill extension
- 118 mm to 260 mm (4 ⁵/₈" to 10 ¹/₄")
- Color selection



* Ask your representative

TECHNICAL SPECIFICATIONS

- 1 Injected rigid polyurethane foam insulation
- 2 Thermal break with solid, kiln-dried pine side and head jambs
- 3 Glass fiber cladding

Energy efficient value of 0.15/0.01 (without glazing)

4 Adjustable bottom weatherstripping

Full-frame compression and magnetic weatherstripping


- 5 Inclined sill with integrated thermal break
- 6 Aluminum or PVC exterior cladding

Frame

Pine 184 mm (7 1/4")

Sill

Aluminum (natural) 184 mm (7 ½/4")



POSSIBLE CONFIGURATIONS (Ask your representative)









- A Single Door
- **B** Combined Door with lateral panel to the left
- C Combined Door with lateral panel to the right
- **D** Combined Door with lateral panels to the left and to the right